

View Online at <https://aerobasegroup.com/nsn/5930-01-190-1232>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.370 inches single mounting facility

**Overall Length:**

3.677 inches

**First Flat Length:**

0.250 inches 1st actuator

**Flat Height:**

0.216 inches 1st actuator

**Shaft Diameter:**

0.250 inches 1st actuator

**Shaft Length:**

0.457 inches 2nd actuator

**Overall Diameter:**

1.030 inches

**Nonturn Device Radius:**

0.432 inches at 6: 00 o'clock

**Individual Section Quantity:**

2

**Nonturn Device Type:**

Tab at 6: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

7 each section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Rotor Through Connection Quantity:**

1 each section

**Switch Actuator Indexing Position Quantity:**

7 1st actuator

**Shaft Type:**

Round, flatted w/through hole 1st actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

30.0 degrees 1st actuator

**Switch Actuator Stop Device Type:**

Fixed stop 1st actuator

**Contact Load Current Rating:**

1.0 amperes resistive load dc at sea level and 500.0 milliamperes inductive load dc at sea level

**Special Features:**

Includes one 4pdt microswitch on rear

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unf single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0