

View Online at <https://aerobasegroup.com/nsn/5930-01-190-4748>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

4.400 inches

Overall Height:

0.960 inches

Overall Width:

0.570 inches

Bushing Length:

1.300 inches

Body Length:

1.800 inches

Body Width:

0.960 inches

Body Height:

0.570 inches

Case Material:

Metal

Actuator Style:

Roller plunger

Actuator Free Position Height:

2.000 inches

Actuator Roller Diameter:

0.406 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

160.0 ounces

Switch Actuating Force:

160.0 ounces

Actuator Movement:

Between 0.050 pretravel inches and 0.250 overtravel inches and 0.250 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

2.500 amperes resistive dc and 1.500 amperes inductive dc

Thread Series Designator:

Uns

Terminal Type And Quantity:

8 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0