NSN 5930-01-190-5298

Push Switch - Page 1 of 2

Uns



View Online at https://aerobasegroup.com/nsn/5930-01-190-5298

Body Style:
Bushing mounted
Hazardous Locations/environmental Protection:
Moisture proof
Body Diameter:
0.630 inches
Bushing Length:
0.440 inches
Body Length:
1.400 inches
Case Material:
Metal
Actuator Length:
0.750 inches
Actuator Style:
Rectangular
Actuator Height:
0.500 inches
Actuator Width:
0.500 inches
Illuminated Actuator Color:
Red single actuator
Actuator Inscription:
Power single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Thready Qty Per Inch (tpi):
32
Thread Size:
0.469 inches
Nonpile-up Contact Arrangement:
1 two circuit, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
3.000 amperes resistive dc and 1.000 amperes lamp dc and 3.000 amperes resistive ac and 1.000 amperes lamp ac
Precious Material And Location:
Contact surfaces gold
Thread Series Designator:

NSN 5930-01-190-5298

Push Switch - Page 2 of 2



Termina	I Type	And (Quantit	٧.
	11 1 1 1 1 1 1	Allu '	wuanni	ν.

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0