

View Online at <https://aerobasegroup.com/nsn/5930-01-190-5301>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Waterproof

**Body Diameter:**

0.562 inches

**Bushing Length:**

Between 0.415 inches and 0.435 inches

**Body Length:**

Between 1.200 inches and 1.260 inches

**Case Material:**

Metal

**Illuminated Actuator Color:**

Yellow single actuator

**Actuator Inscription:**

D single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Rfi shielding

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, two positions momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 0.500 amperes inductive dc

**Special Features:**

Emi shielding

**Precious Material And Location:**

Contacts gold

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

2 tab, solder lug and 6 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0