## NSN 5930-01-190-6500

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-190-6500

**Thread Class:** 

2b single mounting facility

**Thread Length:** 

0.250 inches single mounting facility

**Overall Length:** 

1.999 inches

**Shaft Diameter:** 

0.125 inches single actuator

**Shaft Length:** 

1.000 inches single actuator

**Overall Diameter:** 

0.750 inches

**Individual Section Quantity:** 

2

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

2 each section rear

**Throw Quantity:** 

6 each section rear

**Mounting Method:** 

Threaded bushing single mounting facility

**Thread Size:** 

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level

**Rotor Through Connection Quantity:** 

2 each section

**Switch Actuator Indexing Position Quantity:** 

6 single actuator

**Shaft Type:** 

Round single actuator

**Terminal Type:** 

Tab, solder lug

**Contact Switching Action:** 

Breaks before makes each section rear

**Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Fixed stop-breakoff tab single actuator

**Contact Load Current Rating:** 

250.0 milliamperes resistive load dc at sea level and 125.0 milliamperes inductive load dc at sea level

## NSN 5930-01-190-6500

Rotary Switch - Page 2 of 2



O	_			
Style	υe	sıa	nat	or:

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0