

View Online at <https://aerobasegroup.com/nsn/5930-01-190-7374>

Hazardous Locations/environmental Protection:

Moisture resistant and salt spray resistant and vibration proof

Overall Length:

0.960 inches

Overall Height:

0.375 inches

Body Diameter:

0.660 inches

Mounting Slot Width:

0.104 inches

Distance Between Mounting Facility Centers:

Between 0.937 inches and 0.999 inches

Tempurature Sensing Element Type:

Internal sensor

Operating Tempurature Rating:

Between -65.0 degrees fahrenheit and 450.0 degrees fahrenheit

Mounting Method:

Bracket and slot

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, both positions maintained

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

3.0 amperes resistive load second voltage

Contact Adjustability:

Actuation point not adjustable

Contact Stimulus Rating:

176.00 actuation point degrees fahrenheit

Contact Voltage Rating In Volts:

30.0 dc at sea level second voltage

Media For Which Designed:

Gas

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Style Designator:

Disc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0