## NSN 5930-01-191-3284

Push Switch - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5930-01-191-3284

| View Online at https://aerobasegroup.com/nsn/5930-01-191-3284  |
|--|
| Body Style:  |
| Panel mount  |
| Hazardous Locations/environmental Protection:  |
| Shock resistant and vibration resistant  |
| Overall Length:  |
| 0.740 inches   |
| Overall Height:  |
| 3.060 inches   |
| Overall Width:   |
| 0.740 inches   |
| Body Length:   |
| 0.740 inches   |
| Body Width:  |
| 0.740 inches   |
| Case Material:   |
| Plastic  |
| Actuator Length:   |
| 0.667 inches   |
| Actuator Style:  |
| Rectangular  |
| Actuator Width:  |
| 0.667 inches   |
| Actuator Color:  |
| White single actuator  |
| Maximum Voltage Rating In Volts:   |
| 115.0 ac and 28.0 dc   |
| Inclosure Type:  |
| Fully enclosed   |
| Mounting Method:   |
| Panel  |
| Features Provided:   |
| Rfi shielding  |
| Nonpile-up Contact Arrangement:  |
| 2 pole, double throw, one position momentary single switch unit  |
| Contact Load Current Rating At Maximum Rated Voltage:  |
| 5.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes lamp dc and 5.000 amperes resistive ac and 2.500 amperes |
| inductive ac and 1.500 amperes lamp ac   |
| Precious Material And Location:  |
| Rfi screen surface gold  |
| Terminal Type And Quantity:  |
| 6 pin  |
| Shelf Life:  |

## NSN 5930-01-191-3284

Push Switch - Page 2 of 2



|    | • • |             |    |     |      |
|----|-----|-------------|----|-----|------|
| In | 18  | <i>(</i> )+ | МА | 261 | ıre: |
|    |     |             |    |     |      |

--

Demilitarization:

No

Fiig:

A053a0