

View Online at <https://aerobasegroup.com/nsn/5930-01-191-9678>

**Inside Diameter:**

0.125 inches all connections

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

5.438 inches

**Overall Height:**

3.500 inches

**Overall Width:**

4.312 inches

**Unthreaded Mounting Hole Diameter:**

0.375 inches

**Distance Between Mounting Facility Centers:**

4.875 inches

**End Application:**

4920-01-118-6108 test stand fuel

**Pressure Switch Type:**

Gage

**Operating Temperature Rating:**

Between -40.0 degrees fahrenheit and 140.0 degrees fahrenheit

**Mounting Method:**

Bracket and unthreaded hole

**Features Provided:**

Electrical access port

**Thready Qty Per Inch (tpi):**

27 all pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

45.00 inches of water

**Thread Size:**

0.125 inches all pressure connection

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

15.0 amperes resistive load single voltage

**Contact Adjustability:**

Actuation point adjustable

**Contact Adjustment Range:**

+0.15/+0.50 actuation point inches of water

**Contact Adjustment Type:**

External actuation point screw

**Contact Voltage Rating In Volts:**

480.0 ac at sea level single voltage

**Pressure Connector Type:**

Inverted flare, threaded internal all connections

**Frequency In Hertz:**

60.0 single voltage

**Media For Which Designed:**

Liquid

**Style Designator:**

Cylindrical

**Thread Series Designator:**

Npt all pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0