

View Online at <https://aerobasegroup.com/nsn/5930-01-191-9678>

Inside Diameter:

0.125 inches all connections

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

5.438 inches

Overall Height:

3.500 inches

Overall Width:

4.312 inches

Unthreaded Mounting Hole Diameter:

0.375 inches

Distance Between Mounting Facility Centers:

4.875 inches

End Application:

4920-01-118-6108 test stand fuel

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -40.0 degrees fahrenheit and 140.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

27 all pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

45.00 inches of water

Thread Size:

0.125 inches all pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

15.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+0.15/+0.50 actuation point inches of water

Contact Adjustment Type:

External actuation point screw

Contact Voltage Rating In Volts:

480.0 ac at sea level single voltage

Pressure Connector Type:

Inverted flare, threaded internal all connections

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Npt all pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0