## NSN 5930-01-192-0718

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-192-0718

**Thread Class:** 

2a single mounting facility

**Thread Length:** 

0.531 inches single mounting facility

**Overall Length:** 

3.125 inches

First Flat Length:

0.375 inches single actuator

Flat Height:

0.203 inches single actuator

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

0.500 inches single actuator

**Overall Diameter:** 

1.125 inches

**Individual Section Quantity:** 

5

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Mounting Method:** 

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

**Thread Size:** 

0.312 inches single mounting facility

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:** 

10 single actuator

**Shaft Type:** 

Round, flatted single actuator

**Terminal Type:** 

Tab, solder lug

**Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

**Contact Load Current Rating:** 

6.0 amperes resistive load dc at sea level

**Style Designator:** 

Tap, circular, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

## NSN 5930-01-192-0718

Rotary Switch - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0