## NSN 5930-01-192-1531

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-192-1531

**Thread Class:** 2b single mounting facility **Overall Length:** 4.062 inches **Overall Height:** 2.875 inches **Overall Width:** 2.500 inches **Individual Section Quantity:** 2 **Longest Horizontal Distance Between Mounting Centers:** 1.062 inches single mounting facility **Longest Vertical Distance Between Mounting Centers:** 1.062 inches single mounting facility **Switch Contact Basic Design:** Nonpile-up symmetrical **Mounting Method:** Threaded hole single mounting facility **Features Provided:** Actuator knob and cam actuated Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:** 0.164 inches single mounting facility **Contact Voltage Rating In Volts:** 440.0 highest ac voltage rating at sea level **Mounting Facility Pattern:** Four position rectangular single mounting facility **Cam Actuated Switch Contact Arrangement:** 1 pole, single throw, double make, both positions maintained single switch each section periphery **Switch Actuator Indexing Position Quantity:** 3 single actuator **Switch Actuator Positioning Increment:** 36.0 degrees single actuator **Contact Load Current Rating:** 4.0 amperes inductive load lowest ac voltage rating at sea level **Special Features:** Legend plate reads on, off, standby **Thread Series Designator:** 

Shelf Life:

N/a

Unc single mounting facility

## **NSN 5930-01-192-1531**Rotary Switch - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

Demilitarization:

No

Fiig:

A052b0