NSN 5930-01-192-4355

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-192-4355

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Oiltight
Overall Length:
4.547 inches
Overall Width:
1.625 inches
Housing Height:
1.844 inches
Housing Length:
4.547 inches
Housing Width:
1.625 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.344 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.156 inches
Maximum Voltage Rating In Volts:
600.0 ac and 600.0 dc
600.0 ac and 600.0 dc End Application:
End Application:
End Application: 3930-01-132-6891 aircraft loader
End Application: 3930-01-132-6891 aircraft loader Inclosure Type:
End Application: 3930-01-132-6891 aircraft loader Inclosure Type: Fully enclosed
End Application: 3930-01-132-6891 aircraft loader Inclosure Type: Fully enclosed Mounting Method:
End Application: 3930-01-132-6891 aircraft loader Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole
End Application: 3930-01-132-6891 aircraft loader Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Features Provided:
End Application: 3930-01-132-6891 aircraft loader Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Features Provided: Actuator seal
End Application: 3930-01-132-6891 aircraft loader Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Features Provided: Actuator seal Thread Size:
End Application: 3930-01-132-6891 aircraft loader Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Features Provided: Actuator seal Thread Size: 0.190 inches
End Application: 3930-01-132-6891 aircraft loader Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Features Provided: Actuator seal Thread Size: 0.190 inches Nonpile-up Contact Arrangement:
End Application: 3930-01-132-6891 aircraft loader Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Features Provided: Actuator seal Thread Size: 0.190 inches Nonpile-up Contact Arrangement: 1 two circuit, double make, two positions momentary single switch unit
End Application: 3930-01-132-6891 aircraft loader Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Features Provided: Actuator seal Thread Size: 0.190 inches Nonpile-up Contact Arrangement: 1 two circuit, double make, two positions momentary single switch unit Switch Actuating Force:
End Application: 3930-01-132-6891 aircraft loader Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Features Provided: Actuator seal Thread Size: 0.190 inches Nonpile-up Contact Arrangement: 1 two circuit, double make, two positions momentary single switch unit Switch Actuating Force: 67.2 inch-ounces

Precious Material And Location:

0.100 amperes resistive dc and 1.200 amperes resistive ac

Contacts silver

Thread Series Designator:

Unf

NSN 5930-01-192-4355

Sensitive Switch - Page 2 of 2



Terminal Type And Quantity:
8 screw
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0