# NSN 5930-01-192-7328

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-192-7328

Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Explosion proof and humidity resistant
Overall Length:
3.096 inches
Overall Height:
0.750 inches
Overall Width:
0.750 inches
Body Width:
0.750 inches
Body Height:
0.750 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.100 inches
Actuator Width:
0.620 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
Clear single actuator
Actuator Inscription:
Reset single actuator
Maximum Voltage Rating In Volts:
28.0 dc
End Application:
7025-01-162-5217 multiplexer, upl
Mounting Surface To Terminal End Distance:
2.756 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Full display lens

# NSN 5930-01-192-7328

Push Switch - Page 2 of 2



## **Nonpile-up Contact Arrangement:**

2 pole, double throw, two positions momentary single switch unit

#### **Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 0.500 amperes inductive dc

#### **Precious Material And Location:**

Contacts gold

## **Terminal Type And Quantity:**

1 socket, integrated wire termination

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0