NSN 5930-01-192-7716

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-192-7716

Thread Class:
2b single threaded hole
Inside Diameter:
0.250 inches single connection
Overall Height:
2.094 inches
Overall Width:
2.938 inches
Body Length:
4.750 inches
Pressure Switch Type:
Gage
Mounting Method:
Bracket and unthreaded hole
Thready Qty Per Inch (tpi):
18 single pressure connection
Contact Action Stimulus:
Decrease
Proof Pressure:
160.00 pounds per square inch gage
Thread Size:
0.438 inches single threaded hole
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action
Terminal Type:
Screw
Contact Load Current Rating:
9.6 amperes inductive load fifth voltage
Contact Adjustability:
Actuation point adjustable, preset
Contact Adjustment Range:
+5.00/+75.00 actuation point pounds per square inch gage
Contact Adjustment Type:
External actuation point screw
Contact Stimulus Rating:
5.00 actuation point pounds per square inch gage and 75.00 actuation point pounds per square inch gage and 4.00 differential point
pounds per square inch gage and 20.00 differential point pounds per square inch gage
Contact Voltage Rating In Volts:

Pressure Connector Type:

550.0 dc at sea level eighth voltage

Plain, threaded internal single connection

NSN 5930-01-192-7716

Pressure Switch - Page 2 of 2



Special Features:
P/n 5109598 stamped on name plate
Frequency In Hertz:
60.0 third voltage
Media For Which Designed:
Gas or liquid
Style Designator:
Rectangular
Thread Series Designator:
Unf single threaded hole
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A048b0