

View Online at <https://aerobasegroup.com/nsn/5930-01-192-7718>

Inside Diameter:

0.250 inches single connection

Overall Height:

2.812 inches

Overall Width:

5.188 inches

Body Length:

2.750 inches

Body Height:

2.688 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Longest Horizontal Distance Between Mounting Centers:

2.406 inches

Shortest Horizontal Distance Between Mounting Centers:

0.656 inches

Longest Vertical Distance Between Mounting Centers:

3.281 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Thready Qty Per Inch (tpi):

18 first pressure connection

Contact Action Stimulus:

Decrease

Proof Pressure:

400.00 pounds per square inch gage

Thread Size:

0.750 inches second threaded hole

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

9.6 amperes inductive load fifth voltage

Contact Adjustability:

Actuation point adjustable, preset

Contact Adjustment Range:

+60.00/+350.00 actuation point pounds per square inch gage

Contact Adjustment Type:

Internal actuation point hex nut

Contact Stimulus Rating:

60.00 actuation point pounds per square inch gage and 350.00 actuation point pounds per square inch gage

Contact Voltage Rating In Volts:

550.0 dc at sea level eighth voltage

Pressure Connector Type:

Plain, threaded internal single connection

Frequency In Hertz:

60.0 third voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Npt second threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0