

View Online at <https://aerobasegroup.com/nsn/5930-01-192-7718>

**Inside Diameter:**

0.250 inches single connection

**Overall Height:**

2.812 inches

**Overall Width:**

5.188 inches

**Body Length:**

2.750 inches

**Body Height:**

2.688 inches

**Unthreaded Mounting Hole Diameter:**

0.281 inches

**Longest Horizontal Distance Between Mounting Centers:**

2.406 inches

**Shortest Horizontal Distance Between Mounting Centers:**

0.656 inches

**Longest Vertical Distance Between Mounting Centers:**

3.281 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Bracket and unthreaded hole

**Thready Qty Per Inch (tpi):**

18 first pressure connection

**Contact Action Stimulus:**

Decrease

**Proof Pressure:**

400.00 pounds per square inch gage

**Thread Size:**

0.750 inches second threaded hole

**Mounting Facility Pattern:**

Isosceles triangle

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Screw

**Contact Load Current Rating:**

9.6 amperes inductive load fifth voltage

**Contact Adjustability:**

Actuation point adjustable, preset

**Contact Adjustment Range:**

+60.00/+350.00 actuation point pounds per square inch gage

**Contact Adjustment Type:**

Internal actuation point hex nut

**Contact Stimulus Rating:**

60.00 actuation point pounds per square inch gage and 350.00 actuation point pounds per square inch gage

**Contact Voltage Rating In Volts:**

550.0 dc at sea level eighth voltage

**Pressure Connector Type:**

Plain, threaded internal single connection

**Frequency In Hertz:**

60.0 third voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Thread Series Designator:**

Npt second threaded hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0