

View Online at <https://aerobasegroup.com/nsn/5930-01-193-5238>

**Inside Diameter:**

0.250 inches single connection

**Overall Length:**

2.810 inches

**Overall Height:**

5.750 inches

**Overall Width:**

2.370 inches

**Body Height:**

3.000 inches

**Unthreaded Mounting Hole Diameter:**

0.281 inches

**Longest Horizontal Distance Between Mounting Centers:**

2.720 inches

**Longest Vertical Distance Between Mounting Centers:**

2.720 inches

**Pressure Switch Type:**

Differential

**Mounting Method:**

Bracket and unthreaded hole

**Features Provided:**

Electrical access port

**Thready Qty Per Inch (tpi):**

18 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

12000.00 pounds per square inch gage

**Thread Size:**

0.250 inches single pressure connection

**Mounting Facility Pattern:**

Two position diagonal

**Nonpile-up Contact Arrangement:**

1 pole, double throw, double break/double make, permanent jumper, both positions maintained

**Terminal Type:**

Screw

**Contact Load Current Rating:**

7.5 amperes resistive load second voltage

**Contact Adjustability:**

Actuation point adjustable and deactuation point adjustable

**Contact Adjustment Range:**

+600.00/+6000.00 actuation point pounds per square inch gage and +600.00/+6000.00 deactuation point pounds per square inch gage

**Contact Adjustment Type:**

Internal actuation point screw and internal deactuation point screw

**Contact Voltage Rating In Volts:**

600.0 ac at sea level second voltage

**Pressure Connector Type:**

Plain, threaded internal single connection

**Frequency In Hertz:**

50.0 second voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Thread Series Designator:**

Npt single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0