NSN 5930-01-193-5662

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-193-5662

| Body Style: |
|--|
| Bushing mount |
| Hazardous Locations/environmental Protection: |
| Moisture resistant |
| Overall Length: |
| 0.500 inches |
| Overall Height: |
| 1.043 inches |
| Overall Width: |
| 0.284 inches |
| Bushing Length: |
| 0.280 inches |
| Body Length: |
| 0.500 inches |
| Body Width: |
| 0.284 inches |
| Body Height: |
| 0.434 inches |
| Case Material: |
| Plastic |
| Actuator Style: |
| Round |
| Actuator Diameter: |
| 0.105 inches |
| Actuator Height: |
| 0.200 inches |
| Actuator Position-action Relationship: |
| Up position momentary and down position momentary |
| Maximum Voltage Rating In Volts: |
| 250.0 ac and 28.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Threaded bushing |
| Thready Qty Per Inch (tpi): |
| 40 |
| Thread Size: |
| 0.250 inches |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, both positions maintained single switch unit |
| |

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 200.000 milliamperes inductive ac

NSN 5930-01-193-5662 Toggle Switch - Page 2 of 2



| Precious Material And Location: |
|--|
| Contacts surface silver |
| Thread Series Designator: |
| Uns |
| Terminal Type And Quantity: |
| 5 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A053a0