

View Online at <https://aerobasegroup.com/nsn/5930-01-193-5664>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Water resistant

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Body Length:

1.937 inches

Body Width:

0.687 inches

Body Height:

1.184 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.140 inches

Actuator Style:

Leaf

Actuator Width:

0.219 inches

Actuator Free Position Height:

0.750 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Communications relay

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, two positions momentary single switch unit

Switch Release Force:

0.5 ounces

Switch Actuating Force:

3.5 ounces

Actuator Movement:

Between 0.406 pretravel inches and 0.156 overtravel inches and 0.093 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 1.000 amperes inductive dc and 1.500 amperes lamp dc and 15.000 amperes resistive ac and 15.000 amperes inductive ac and 1.500 amperes lamp ac

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0