NSN 5930-01-193-5677

Push Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-193-5677

Center To Center Distance Between Mounting Facilities Parallel To Width: 1.250 inches Body Length: 2.120 inches Body Width: 1.750 inches Body Height: 1.620 inches Actuator Height: 0.310 inches Actuator Inscription: Gtry aft single actuator Maximum Voltage Rating In Volts: 440.0 ac and 355.0 dc Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 2 pole, single throw, normally open, double make, momentary action single switch unit Contact Load Current Rating At Maximum Rated Voltage: 0.500 amperes inductive dc and 5.000 amperes inductive ac Terminal Type And Quantity: 4 tab w/screw Shelf Life: N/a Unit Of Measure:	Center To Center Distance Between Mounting Facilities Parallel To Length:
1.250 inches Body Length: 2.120 inches Body Width: 1.750 inches Body Height: 1.620 inches Actuator Height: 0.310 inches Actuator Inscription: Gtry aft single actuator Maximum Voltage Rating In Volts: 440.0 ac and 355.0 dc Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 2 pole, single throw, normally open, double make, momentary action single switch unit Contact Load Current Rating At Maximum Rated Voltage: 0.500 amperes inductive dc and 5.000 amperes inductive ac Terminal Type And Quantity: 4 tab w/screw Shelf Life: N/a Unit Of Measure:	1.620 inches
1.250 inches Body Length: 2.120 inches Body Width: 1.750 inches Body Height: 1.620 inches Actuator Height: 0.310 inches Actuator Inscription: Gtry aft single actuator Maximum Voltage Rating In Volts: 440.0 ac and 355.0 dc Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 2 pole, single throw, normally open, double make, momentary action single switch unit Contact Load Current Rating At Maximum Rated Voltage: 0.500 amperes inductive dc and 5.000 amperes inductive ac Terminal Type And Quantity: 4 tab w/screw Shelf Life: N/a Unit Of Measure:	Center To Center Distance Between Mounting Facilities Parallel To Width:
2.120 inches Body Width: 1.750 inches Body Height: 1.620 inches Actuator Height: 0.310 inches Actuator Inscription: Gtry aft single actuator Maximum Voltage Rating In Volts: 440.0 ac and 355.0 dc Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 2 pole, single throw, normally open, double make, momentary action single switch unit Contact Load Current Rating At Maximum Rated Voltage: 0.500 amperes inductive dc and 5.000 amperes inductive ac Terminal Type And Quantity: 4 tab w/screw Shelf Life: N/a Unit Of Measure:	1.250 inches
2.120 inches Body Width: 1.750 inches Body Height: 1.620 inches Actuator Height: 0.310 inches Actuator Inscription: Gtry aft single actuator Maximum Voltage Rating In Volts: 440.0 ac and 355.0 dc Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 2 pole, single throw, normally open, double make, momentary action single switch unit Contact Load Current Rating At Maximum Rated Voltage: 0.500 amperes inductive dc and 5.000 amperes inductive ac Terminal Type And Quantity: 4 tab w/screw Shelf Life: N/a Unit Of Measure:	Body Length:
1.750 inches Body Height: 1.620 inches Actuator Height: 0.310 inches Actuator Inscription: Gtry aft single actuator Maximum Voltage Rating In Volts: 440.0 ac and 355.0 dc Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 2 pole, single throw, normally open, double make, momentary action single switch unit Contact Load Current Rating At Maximum Rated Voltage: 0.500 amperes inductive dc and 5.000 amperes inductive ac Terminal Type And Quantity: 4 tab w/screw Shelf Life: N/a Unit Of Measure:	2.120 inches
Body Height: 1.620 inches Actuator Height: 0.310 inches Actuator Inscription: Gtry aft single actuator Maximum Voltage Rating In Volts: 440.0 ac and 355.0 dc Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 2 pole, single throw, normally open, double make, momentary action single switch unit Contact Load Current Rating At Maximum Rated Voltage: 0.500 amperes inductive dc and 5.000 amperes inductive ac Terminal Type And Quantity: 4 tab w/screw Shelf Life: N/a Unit Of Measure:	Body Width:
1.620 inches Actuator Height: 0.310 inches Actuator Inscription: Gtry aft single actuator Maximum Voltage Rating In Volts: 440.0 ac and 355.0 dc Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 2 pole, single throw, normally open, double make, momentary action single switch unit Contact Load Current Rating At Maximum Rated Voltage: 0.500 amperes inductive dc and 5.000 amperes inductive ac Terminal Type And Quantity: 4 tab w/screw Shelf Life: N/a Unit Of Measure:	1.750 inches
Actuator Height: 0.310 inches Actuator Inscription: Gtry aft single actuator Maximum Voltage Rating In Volts: 440.0 ac and 355.0 dc Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 2 pole, single throw, normally open, double make, momentary action single switch unit Contact Load Current Rating At Maximum Rated Voltage: 0.500 amperes inductive dc and 5.000 amperes inductive ac Terminal Type And Quantity: 4 tab w/screw Shelf Life: N/a Unit Of Measure:	Body Height:
O.310 inches Actuator Inscription: Gtry aft single actuator Maximum Voltage Rating In Volts: 440.0 ac and 355.0 dc Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 2 pole, single throw, normally open, double make, momentary action single switch unit Contact Load Current Rating At Maximum Rated Voltage: 0.500 amperes inductive dc and 5.000 amperes inductive ac Terminal Type And Quantity: 4 tab w/screw Shelf Life: N/a Unit Of Measure:	1.620 inches
Actuator Inscription: Gtry aft single actuator Maximum Voltage Rating In Volts: 440.0 ac and 355.0 dc Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 2 pole, single throw, normally open, double make, momentary action single switch unit Contact Load Current Rating At Maximum Rated Voltage: 0.500 amperes inductive dc and 5.000 amperes inductive ac Terminal Type And Quantity: 4 tab w/screw Shelf Life: N/a Unit Of Measure:	Actuator Height:
Maximum Voltage Rating In Volts: 440.0 ac and 355.0 dc Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 2 pole, single throw, normally open, double make, momentary action single switch unit Contact Load Current Rating At Maximum Rated Voltage: 0.500 amperes inductive dc and 5.000 amperes inductive ac Terminal Type And Quantity: 4 tab w/screw Shelf Life: N/a Unit Of Measure:	0.310 inches
Maximum Voltage Rating In Volts: 440.0 ac and 355.0 dc Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 2 pole, single throw, normally open, double make, momentary action single switch unit Contact Load Current Rating At Maximum Rated Voltage: 0.500 amperes inductive dc and 5.000 amperes inductive ac Terminal Type And Quantity: 4 tab w/screw Shelf Life: N/a Unit Of Measure:	Actuator Inscription:
440.0 ac and 355.0 dc Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 2 pole, single throw, normally open, double make, momentary action single switch unit Contact Load Current Rating At Maximum Rated Voltage: 0.500 amperes inductive dc and 5.000 amperes inductive ac Terminal Type And Quantity: 4 tab w/screw Shelf Life: N/a Unit Of Measure:	Gtry aft single actuator
Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 2 pole, single throw, normally open, double make, momentary action single switch unit Contact Load Current Rating At Maximum Rated Voltage: 0.500 amperes inductive dc and 5.000 amperes inductive ac Terminal Type And Quantity: 4 tab w/screw Shelf Life: N/a Unit Of Measure:	Maximum Voltage Rating In Volts:
Fully enclosed Nonpile-up Contact Arrangement: 2 pole, single throw, normally open, double make, momentary action single switch unit Contact Load Current Rating At Maximum Rated Voltage: 0.500 amperes inductive dc and 5.000 amperes inductive ac Terminal Type And Quantity: 4 tab w/screw Shelf Life: N/a Unit Of Measure:	440.0 ac and 355.0 dc
Nonpile-up Contact Arrangement: 2 pole, single throw, normally open, double make, momentary action single switch unit Contact Load Current Rating At Maximum Rated Voltage: 0.500 amperes inductive dc and 5.000 amperes inductive ac Terminal Type And Quantity: 4 tab w/screw Shelf Life: N/a Unit Of Measure:	Inclosure Type:
2 pole, single throw, normally open, double make, momentary action single switch unit Contact Load Current Rating At Maximum Rated Voltage: 0.500 amperes inductive dc and 5.000 amperes inductive ac Terminal Type And Quantity: 4 tab w/screw Shelf Life: N/a Unit Of Measure:	Fully enclosed
Contact Load Current Rating At Maximum Rated Voltage: 0.500 amperes inductive dc and 5.000 amperes inductive ac Terminal Type And Quantity: 4 tab w/screw Shelf Life: N/a Unit Of Measure:	Nonpile-up Contact Arrangement:
0.500 amperes inductive dc and 5.000 amperes inductive ac Terminal Type And Quantity: 4 tab w/screw Shelf Life: N/a Unit Of Measure:	2 pole, single throw, normally open, double make, momentary action single switch unit
Terminal Type And Quantity: 4 tab w/screw Shelf Life: N/a Unit Of Measure:	Contact Load Current Rating At Maximum Rated Voltage:
4 tab w/screw Shelf Life: N/a Unit Of Measure:	0.500 amperes inductive dc and 5.000 amperes inductive ac
Shelf Life: N/a Unit Of Measure:	Terminal Type And Quantity:
N/a Unit Of Measure:	4 tab w/screw
Unit Of Measure:	Shelf Life:
	N/a
 Demilitarization:	Unit Of Measure:
Demilitarization:	
	Demilitarization:
No	No
Fiig:	Fiig:
A053a0	A053a0