NSN 5930-01-193-5678

Push Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-193-5678

Center To Center Distance Between Mounting Facilities Parallel To Length:
1.620 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.250 inches
Body Length:
2.120 inches
Body Width:
1.750 inches
Body Height: 1.620 inches
Actuator Height:
0.310 inches
Actuator Inscription:
Gtry fwd single actuator
Maximum Voltage Rating In Volts:
440.0 ac and 355.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
2 pole, single throw, normally open, double make, momentary action single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
Contact Load Current Rating At Maximum Rated Voltage: 0.500 amperes inductive dc and 5.000 amperes inductive ac
Contact Load Current Rating At Maximum Rated Voltage:
Contact Load Current Rating At Maximum Rated Voltage: 0.500 amperes inductive dc and 5.000 amperes inductive ac
Contact Load Current Rating At Maximum Rated Voltage: 0.500 amperes inductive dc and 5.000 amperes inductive ac Terminal Type And Quantity:
Contact Load Current Rating At Maximum Rated Voltage: 0.500 amperes inductive dc and 5.000 amperes inductive ac Terminal Type And Quantity: 4 tab w/screw
Contact Load Current Rating At Maximum Rated Voltage: 0.500 amperes inductive dc and 5.000 amperes inductive ac Terminal Type And Quantity: 4 tab w/screw Shelf Life:
Contact Load Current Rating At Maximum Rated Voltage: 0.500 amperes inductive dc and 5.000 amperes inductive ac Terminal Type And Quantity: 4 tab w/screw Shelf Life: N/a
Contact Load Current Rating At Maximum Rated Voltage: 0.500 amperes inductive dc and 5.000 amperes inductive ac Terminal Type And Quantity: 4 tab w/screw Shelf Life: N/a
Contact Load Current Rating At Maximum Rated Voltage: 0.500 amperes inductive dc and 5.000 amperes inductive ac Terminal Type And Quantity: 4 tab w/screw Shelf Life: N/a Unit Of Measure:
Contact Load Current Rating At Maximum Rated Voltage: 0.500 amperes inductive dc and 5.000 amperes inductive ac Terminal Type And Quantity: 4 tab w/screw Shelf Life: N/a Unit Of Measure: Demilitarization:
Contact Load Current Rating At Maximum Rated Voltage: 0.500 amperes inductive dc and 5.000 amperes inductive ac Terminal Type And Quantity: 4 tab w/screw Shelf Life: N/a Unit Of Measure: Demilitarization: No