NSN 5930-01-193-8215

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-193-8215
Overall Length:
3.100 inches
Outside Diameter:
0.250 inches single connection
Body Diameter:
1.370 inches
Body Length:
1.950 inches
Overall Diameter:
1.920 inches
Unthreaded Mounting Hole Diameter:
0.062 inches
Distance Between Mounting Facility Centers:
0.625 inches
Pressure Switch Type:
Absolute
Operating Tempurature Rating:
Between -0.0 degrees fahrenheit and 120.0 degrees fahrenheit
Mounting Method:
Flange and unthreaded hole
Features Provided:
Electrical access port
Thready Qty Per Inch (tpi):
18 single pressure connection
Contact Action Stimulus:
Increase
Proof Pressure:
24.00 inches of mercury
Thread Size:
0.250 inches single pressure connection
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Wire lead

Contact Load Current Rating:

1.0 amperes resistive load single voltage and 4.0 milliamperes lamp load single voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

21.00 actuation point inches of mercury and 18.00 deactuation point inches of mercury

NSN 5930-01-193-8215

Pressure Switch - Page 2 of 2

No Fiig: A048b0



Contact Voltage Rating In Volts:
125.0 ac at sea level single voltage
Pressure Connector Type:
External seat-gasket seal, threaded external single connection
Frequency In Hertz:
60.0 single voltage
Media For Which Designed:
Gas
Style Designator:
Cylindrical
Thread Series Designator:
Npt single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: