## NSN 5930-01-193-8271



Rotary Switch - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5930-01-193-8271
Thread Class:
2b 1st mounting facility
Thread Length:
0.438 inches 2nd mounting facility
Overall Length:
10.626 inches
Overall Height:
3.750 inches
Overall Width:
3.750 inches
Individual Section Quantity:
15
Longest Horizontal Distance Between Mounting Centers:
2.297 inches 1st mounting facility
Longest Vertical Distance Between Mounting Centers:
2.297 inches 1st mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Mounting Facility Circle Radius:
0.906 inches 2nd mounting facility
Mounting Method:
Threaded stud 2nd mounting facility
Features Provided:
Actuator knob
Thready Qty Per Inch (tpi):
24 1st mounting facility
Thread Size:
0.190 inches 2nd mounting facility
Contact Voltage Rating In Volts:
30.0 dc at sea level
Mounting Facility Pattern:

Four position rectangular 1st mounting facility

**Switch Actuator Indexing Position Quantity:** 

12 single actuator

**Terminal Type:** 

Screw

**Contact Switching Action:** 

Breaks before makes each section rear

**Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Adjustable stop single actuator

## NSN 5930-01-193-8271

Rotary Switch - Page 2 of 2



## **Contact Load Current Rating:**

7.5 amperes resistive load ac at sea level

**Precious Material And Location:** 

Contact surfaces silver

**Precious Material:** 

Silver

Style Designator:

Tap, circuit selector

**Thread Series Designator:** 

Unf 2nd mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A052b0