

View Online at <https://aerobasegroup.com/nsn/5930-01-193-8272>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.344 inches single mounting facility and 0.391 inches single mounting facility

**Overall Length:**

1.861 inches

**Overall Height:**

1.440 inches

**Overall Width:**

1.300 inches

**First Flat Length:**

0.328 inches single actuator

**Flat Height:**

0.211 inches single actuator and 0.221 inches single actuator

**Shaft Diameter:**

0.247 inches single actuator and 0.251 inches single actuator

**Shaft Length:**

0.414 inches single actuator

**Nonturn Device Radius:**

0.531 inches at 3:00 o'clock

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Tab at 3:00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section rear

**Throw Quantity:**

6 single section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

300.0 highest ac voltage rating at sea level

**Shaft Flat/slot Angular Location:**

345.0 degrees from nonturn device single actuator

**Switch Actuator Indexing Position Quantity:**

6 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Contact Load Current Rating:**

50.0 milliamperes resistive load highest ac voltage rating at sea level

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0