NSN 5930-01-193-8392

Hazardous Locations/environmental Protection:

Push Switch - Page 1 of 2

Explosion proof and humidity resistant

Body Style:Panel mounted

Overall Length: 2.150 inches



View Online at https://aerobasegroup.com/nsn/5930-01-193-8392

Overall Height:
1.000 inches
Overall Width:
0.750 inches
Body Width:
0.750 inches
Body Height:
1.000 inches
Actuator Length:
0.835 inches
Actuator Style:
Rectangular
Actuator Height:
0.150 inches
Actuator Width:
0.585 inches
Illuminated Actuator Color:
Red single actuator
Actuator Inscription:
Alarm single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
End Application:
Receiving set, countermeasure an/wlq- (v)
Mounting Surface To Terminal End Distance:
2.000 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Full display lens
Nonpile-up Contact Arrangement:
2 pole, double throw, two positions momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
1.000 amperes resistive dc and 0.500 amperes inductive dc and 1.000 amperes resistive ac and 0.500 amperes inductive ac

NSN 5930-01-193-8392

Push Switch - Page 2 of 2



Emi shielding required

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0