

View Online at <https://aerobasegroup.com/nsn/5930-01-193-8393>

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

Overall Length:

2.150 inches

Overall Height:

1.000 inches

Overall Width:

0.750 inches

Body Width:

0.750 inches

Body Height:

1.000 inches

Actuator Length:

0.835 inches

Actuator Style:

Rectangular

Actuator Height:

0.150 inches

Actuator Width:

0.585 inches

Illuminated Actuator Color:

Red single actuator

Actuator Inscription:

Kybd single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Receiving set, countermeasure an/wlq- (v)

Mounting Surface To Terminal End Distance:

2.000 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Full display lens

Nonpile-up Contact Arrangement:

2 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc and 1.000 amperes resistive ac and 0.500 amperes inductive ac

Special Features:

Emi shielding required

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0