## NSN 5930-01-193-8394

Push Switch - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5930-01-193-8394

## **Body Style:**

Panel mounted

## Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

## **Overall Length:**

2.150 inches

#### **Overall Height:**

1.000 inches

#### **Overall Width:**

0.750 inches

#### **Body Width:**

0.750 inches

#### **Body Height:**

1.000 inches

#### Actuator Length:

## 0.835 inches

Actuator Style:

Rectangular

## Actuator Height:

0.150 inches

## Actuator Width:

0.585 inches

#### Illuminated Actuator Color:

Red single actuator

#### **Actuator Inscription:**

Eqpt single actuator

#### Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

#### **End Application:**

Receiving set, countermeasure an/wlq- (v)

#### Mounting Surface To Terminal End Distance:

2.000 inches

Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Panel

## **Features Provided:**

Full display lens

## Nonpile-up Contact Arrangement:

2 pole, double throw, two positions momentary single switch unit

## Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc and 1.000 amperes resistive ac and 0.500 amperes inductive ac

# NSN 5930-01-193-8394

Push Switch - Page 2 of 2



Special Features:

Emi shielding required

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0