NSN 5930-01-194-1125

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-194-1125

Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Explosion proof and humidity resistant
Overall Length:
5.110 inches
Overall Height:
0.750 inches
Overall Width:
0.750 inches
Body Width:
0.679 inches
Body Height:
0.679 inches
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
Between 0.090 inches and 0.120 inches
Actuator Width:
0.620 inches
Actuator Color:
Black single actuator and black single actuator
Illuminated Actuator Color:
Black single actuator and black single actuator
Actuator Inscription:
On/avail single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
4.990 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Horizontal split lens and holding solenoid
Nonpile-up Contact Arrangement:
3 pole, double throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac and 1.000 amperes lamp ac

NSN 5930-01-194-1125

Push Switch - Page 2 of 2



Precious Material And Location:
Contacts silver
Terminal Type And Quantity:
1 socket, integrated wire termination
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0