NSN 5930-01-195-2048

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-195-2048

Thread	Class:
--------	--------

2a single mounting facility

Thread Length:

0.344 inches single mounting facility and 0.391 inches single mounting facility

Hazardous Locations/environmental Protection:

Moisture resistant

Overall Length:

1.861 inches

Overall Height:

1.440 inches

Overall Width:

1.300 inches

First Flat Length:

0.328 inches single actuator

Flat Height:

0.211 inches single actuator and 0.221 inches single actuator

Shaft Diameter:

0.247 inches single actuator and 0.251 inches single actuator

Shaft Length:

3.900 inches single actuator and 4.370 inches single actuator

Nonturn Device Radius:

0.531 inches at 3: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 3: 00 o'clock

Operating Tempurature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section rear

Throw Quantity:

2 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

300.0 ac at sea level

Shaft Flat/slot Angular Location:

60.0 degrees from nonturn device single actuator

NSN 5930-01-195-2048Rotary Switch - Page 2 of 2



Rotor Through Connection Quantity:
1 single section
Switch Actuator Indexing Position Quantity:
2 single actuator
Shaft Type:
Round, flatted single actuator
Terminal Type:
Tab, solder lug
Contact Switching Action:
Breaks before makes single section rear
Switch Actuator Positioning Increment:
30.0 degrees single actuator
Detent Rotational Torque Range:
+1.000/+6.000 inch-pounds single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
500.0 milliamperes resistive load dc at sea level and 50.0 milliamperes inductive load dc at sea level
Precious Material And Location:
Contacts silver
Precious Material:
Silver
Style Designator:
Circular wafer, bushing mount
Thread Series Designator:
Unef single mounting facility
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A052b0