

View Online at <https://aerobasegroup.com/nsn/5930-01-196-0896>

Thread Class:

2b 1st mounting facility

Thread Length:

0.438 inches 3rd mounting facility

Overall Length:

6.251 inches

Overall Diameter:

3.750 inches

Individual Section Quantity:

5

Longest Horizontal Distance Between Mounting Centers:

2.812 inches 1st mounting facility

Longest Vertical Distance Between Mounting Centers:

2.812 inches 1st mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section rear

Throw Quantity:

3 each section rear

Mounting Facility Circle Radius:

0.906 inches 3rd mounting facility

Mounting Method:

Threaded stud 3rd mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

24 1st mounting facility

Thread Size:

0.625 inches 2nd mounting facility

Contact Voltage Rating In Volts:

30.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular 1st mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Terminal Type:

Screw

Contact Switching Action:

Makes before breaks, breaks before makes each section rear

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

10.0 amperes resistive load dc at sea level

Precious Material And Location:

Rotor and stator contact surfaces silver

Precious Material:

Silver

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unf 3rd mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0