NSN 5930-01-196-6917

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-196-6917

| Body Style: |
|---|
| Panel mount |
| Hazardous Locations/environmental Protection: |
| Shock resistant |
| Overall Length: |
| 1.200 inches |
| Overall Height: |
| 3.250 inches |
| Overall Width: |
| 0.960 inches |
| Body Length: |
| 1.090 inches |
| Body Width: |
| 0.960 inches |
| Actuator Length: |
| 1.040 inches |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| 0.140 inches |
| Actuator Width: |
| 0.800 inches |
| Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| End Application: |
| 1430-01-078-9643 radar set |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel |
| Nonpile-up Contact Arrangement: |
| 4 pole, double throw, both positions maintained single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 ampere |
| inductive ac and 1.500 amperes lamp ac |
| Test Data Document: |
| |

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

12 turret and 5 tab, solder lug

Specification Data:

81349-mil-s-22885/9 government specification

Shelf Life:

N/a

NSN 5930-01-196-6917

Push Switch - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A053a0