

View Online at <https://aerobasegroup.com/nsn/5930-01-196-9262>

Thread Class:

3a single pressure connection

Overall Length:

2.688 inches

Outside Diameter:

0.4375 inches single connection

Body Length:

Between 1.875 inches and 2.400 inches

Overall Diameter:

1.150 inches

Pressure Switch Type:

Gage

Width Across Flats:

Between 0.684 inches and 1.000 inches

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 275.0 degrees fahrenheit

Mounting Method:

Inlet connection

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Proof Pressure:

120.00 pounds per square inch

Thread Size:

0.4375 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

800.00 pounds per square inch

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

3.0 amperes resistive load single voltage and 1.0 amperes inductive load single voltage

Contact Adjustability:

Actuation point not adjustable

Contact Stimulus Rating:

11.00 actuation point pounds per square inch

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Test Data Document:

81349-mil-s-9395 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unjf single pressure connection

Specification Data:

81349-mil-s-9395/27 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0