

View Online at <https://aerobasegroup.com/nsn/5930-01-196-9292>

Thread Class:

3a single pressure connection

Overall Length:

2.703 inches

Outside Diameter:

0.437 inches single connection

Pressure Switch Type:

Gage

Width Across Flats:

0.750 inches

Mounting Method:

Input port

Contact Action Stimulus:

Increase

Proof Pressure:

3000.00 pounds per square inch gage

Thread Size:

0.437 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, two positions momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

50.0 milliamperes resistive load single voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

75.00 actuation point pounds per square inch gage and 60.00 deactuation point pounds per square inch gage

Contact Voltage Rating In Volts:

24.0 dc at sea level single voltage

Pressure Connector Type:

Inverted flare, threaded external single connection

Special Features:

0.038 in. Min and 0.050 in. Maximum diameter lock wire holes in two places

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unjf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0