NSN 5930-01-196-9297

Hazardous Locations/environmental Protection:

Contact Voltage Rating In Volts:

120.0 ac at sea level first voltage240.0 ac at sea level second voltage

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-196-9297

| Vibration resistant |
|---|
| Overall Length: |
| 5.062 inches |
| Overall Height: |
| 3.906 inches |
| Overall Width: |
| 3.312 inches |
| Body Length: |
| 5.062 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.201 inches |
| Longest Horizontal Distance Between Mounting Centers: |
| 4.375 inches |
| Longest Vertical Distance Between Mounting Centers: |
| 3.250 inches |
| Tempurature Sensing Element Type: |
| Internal sensor |
| Operating Tempurature Rating: |
| Between -30.0 degrees fahrenheit and 130.0 degrees fahrenheit |
| Mounting Method: |
| Unthreaded hole |
| Features Provided: |
| Electrical access port |
| Contact Action Stimulus: |
| Increase |
| Mounting Facility Pattern: |
| Two position diagonal |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, one position momentary |
| Terminal Type: |
| Quick disconnect, male |
| Contact Load Current Rating: |
| 10.0 amperes resistive load first voltage5.0 amperes resistive load second voltage |
| Contact Adjustability: |
| Actuation point adjustable and deactuation point adjustable |
| Contact Adjustment Range: |
| -90.00/+700.00 actuation point degrees fahrenheit and -90.00/+700.00 deactuation point degrees fahrenheit |
| Contact Adjustment Type: |
| External actuation point dial and external deactuation point dial |

NSN 5930-01-196-9297

Thermostatic Switch - Page 2 of 2



| Media For Which Designed: |
|---------------------------|
| Gas |
| Style Designator: |
| Rectangular |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A048b0