NSN 5930-01-196-9297

Hazardous Locations/environmental Protection:

Contact Voltage Rating In Volts:

120.0 ac at sea level first voltage240.0 ac at sea level second voltage

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-196-9297

Vibration resistant
Overall Length:
5.062 inches
Overall Height:
3.906 inches
Overall Width:
3.312 inches
Body Length:
5.062 inches
Unthreaded Mounting Hole Diameter:
0.201 inches
Longest Horizontal Distance Between Mounting Centers:
4.375 inches
Longest Vertical Distance Between Mounting Centers:
3.250 inches
Tempurature Sensing Element Type:
Internal sensor
Operating Tempurature Rating:
Between -30.0 degrees fahrenheit and 130.0 degrees fahrenheit
Mounting Method:
Unthreaded hole
Features Provided:
Electrical access port
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position diagonal
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Quick disconnect, male
Contact Load Current Rating:
10.0 amperes resistive load first voltage5.0 amperes resistive load second voltage
Contact Adjustability:
Actuation point adjustable and deactuation point adjustable
Contact Adjustment Range:
-90.00/+700.00 actuation point degrees fahrenheit and -90.00/+700.00 deactuation point degrees fahrenheit
Contact Adjustment Type:
External actuation point dial and external deactuation point dial

NSN 5930-01-196-9297

Thermostatic Switch - Page 2 of 2



Media For Which Designed:
Gas
Style Designator:
Rectangular
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0