

View Online at <https://aerobasegroup.com/nsn/5930-01-196-9297>

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

5.062 inches

Overall Height:

3.906 inches

Overall Width:

3.312 inches

Body Length:

5.062 inches

Unthreaded Mounting Hole Diameter:

0.201 inches

Longest Horizontal Distance Between Mounting Centers:

4.375 inches

Longest Vertical Distance Between Mounting Centers:

3.250 inches

Temperature Sensing Element Type:

Internal sensor

Operating Temperature Rating:

Between -30.0 degrees fahrenheit and 130.0 degrees fahrenheit

Mounting Method:

Unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Quick disconnect, male

Contact Load Current Rating:

10.0 amperes resistive load first voltage5.0 amperes resistive load second voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

-90.00/+700.00 actuation point degrees fahrenheit and -90.00/+700.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External actuation point dial and external deactuation point dial

Contact Voltage Rating In Volts:

120.0 ac at sea level first voltage240.0 ac at sea level second voltage

Media For Which Designed:

Gas

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0