

View Online at <https://aerobasegroup.com/nsn/5930-01-197-2209>

Thread Class:

2a single threaded stud

Hazardous Locations/environmental Protection:

Moisture resistant and salt spray resistant and vibration resistant and watertight

Overall Length:

3.595 inches

Body Diameter:

0.670 centimeters

Body Length:

2.500 inches

Tempurature Sensing Element Type:

Internal sensor

Width Across Flats:

1.135 inches

Operating Tempurature Rating:

Between -75.0 degrees fahrenheit and 500.0 degrees fahrenheit

Mounting Method:

Threaded stud

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Thread Size:

0.750 inches single threaded stud

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

5.0 amperes resistive load second voltage and 2.5 amperes inductive load second voltage and 1.0 amperes lamp load second voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

85.00 actuation point degrees fahrenheit and 75.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/flange

Test Data Document:

81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unf single threaded stud

Specification Data:

81349-mil-s-24236/2 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0