

View Online at <https://aerobasegroup.com/nsn/5930-01-197-4155>

Inside Diameter:

0.125 inches single connection

Overall Length:

3.156 inches

Body Diameter:

0.875 inches

Body Length:

1.750 inches

Overall Diameter:

1.625 inches

Distance Between Mounting Facility Centers:

1.375 inches

End Application:

6530-01-147-9531

Pressure Switch Type:

Differential

Mounting Facility Circle Radius:

0.812 inches

Mounting Method:

Flange

Cubic Measure:

16.600 cubic inches

Thready Qty Per Inch (tpi):

27 single threaded hole

Contact Action Stimulus:

Increase

Proof Pressure:

30.00 inches of mercury

Thread Size:

0.125 inches single threaded hole

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Quick disconnect, male

Contact Load Current Rating:

1.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point adjustable, preset

Contact Adjustment Type:

Internal actuation point screw

Contact Stimulus Rating:

-10.00 actuation point inches of mercury

Contact Voltage Rating In Volts:

125.0 ac at sea level single voltage

Pressure Connector Type:

Plain, threaded internal single connection

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Gas or liquid

Precious Material And Location:

Internal contacts gold

Precious Material:

Gold

Style Designator:

Cylindrical w/flange

Thread Series Designator:

Npt single threaded hole

Purchase Description Identification:

02964-p-83866-001

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0