

View Online at <https://aerobasegroup.com/nsn/5930-01-197-8115>

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Explosion proof and humidity resistant and salt spray resistant

**Overall Length:**

Between 1.980 inches and 2.020 inches

**Overall Height:**

Between 3.150 inches and 3.290 inches

**Overall Width:**

1.750 inches

**Body Length:**

Between 1.980 inches and 2.020 inches

**Body Width:**

Between 1.735 inches and 1.760 inches

**Body Height:**

Between 2.670 inches and 2.730 inches

**Actuator Length:**

1.125 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

Between 0.460 inches and 0.500 inches

**Actuator Width:**

1.125 inches

**Actuator Color:**

Green single actuator and white single actuator

**Illuminated Actuator Color:**

Green single actuator and white single actuator

**Actuator Inscription:**

Avail/on line single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

2.000 amperes resistive dc and 1.000 amperes inductive dc and 2.000 amperes resistive ac and 1.000 amperes inductive ac

**Special Features:**

Mounting flange has four 0.171 in. Diameter mtg holes on 1.125 in. By 1.125 in. Mtg centers; horizontal split lens

**Terminal Type And Quantity:**

1 socket, integrated wire termination

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0