

View Online at <https://aerobasegroup.com/nsn/5930-01-197-8115>

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant and salt spray resistant

Overall Length:

Between 1.980 inches and 2.020 inches

Overall Height:

Between 3.150 inches and 3.290 inches

Overall Width:

1.750 inches

Body Length:

Between 1.980 inches and 2.020 inches

Body Width:

Between 1.735 inches and 1.760 inches

Body Height:

Between 2.670 inches and 2.730 inches

Actuator Length:

1.125 inches

Actuator Style:

Rectangular

Actuator Height:

Between 0.460 inches and 0.500 inches

Actuator Width:

1.125 inches

Actuator Color:

Green single actuator and white single actuator

Illuminated Actuator Color:

Green single actuator and white single actuator

Actuator Inscription:

Avail/on line single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 1.000 amperes inductive dc and 2.000 amperes resistive ac and 1.000 amperes inductive ac

Special Features:

Mounting flange has four 0.171 in. Diameter mtg holes on 1.125 in. By 1.125 in. Mtg centers; horizontal split lens

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0