

View Online at <https://aerobasegroup.com/nsn/5930-01-198-1539>

**Body Style:**

Printed circuit

**Overall Length:**

0.280 inches

**Overall Height:**

Between 0.400 inches and 0.460 inches

**Overall Width:**

0.380 inches

**Body Length:**

Between 0.260 inches and 0.300 inches

**Body Width:**

Between 0.360 inches and 0.400 inches

**Body Height:**

Between 0.240 inches and 0.300 inches

**Case Material:**

Plastic

**Switch Actuator Quantity:**

2

**Actuator Style:**

Rectangular

**Actuator Height:**

Between 0.195 inches and 0.205 inches

**Actuator Width:**

0.070 inches

**Actuator Position-action Relationship:**

Left position maintained and right position maintained

**Maximum Voltage Rating In Volts:**

6.0 dc and 24.0 dc

**Inclosure Type:**

Hermetically sealed

**Mounting Method:**

Printed circuit

**Nonpile-up Contact Arrangement:**

1 pole, single throw, both positions maintained 2nd switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

100.0 milliamperes resistive dc and 25.0 milliamperes resistive dc

**Precious Material And Location:**

Contact surfaces gold

**Test Data Document:**

81349-mil-s-83504 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

4 printed circuit

**Specification Data:**

81349-mil-s-83504/2 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0