

View Online at <https://aerobasegroup.com/nsn/5930-01-198-1552>

**Inside Diameter:**

0.250 inches single connection

**Overall Length:**

4.170 inches

**Overall Height:**

5.630 inches

**Body Height:**

4.920 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.280 inches and 0.430 inches

**Longest Horizontal Distance Between Mounting Centers:**

3.540 inches

**Longest Vertical Distance Between Mounting Centers:**

2.910 inches

**Pressure Switch Type:**

Differential

**Mounting Method:**

Unthreaded hole

**Thready Qty Per Inch (tpi):**

18 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

5600.00 pounds per square inch

**Thread Size:**

0.250 inches single pressure connection

**Mounting Facility Pattern:**

Two position diagonal

**Terminal Type:**

Screw

**Contact Load Current Rating:**

10.0 amperes resistive load first voltage

**Contact Adjustability:**

Actuation point adjustable, preset and deactuation point adjustable, preset

**Contact Adjustment Range:**

+280.00/+5600.00 actuation point pounds per square inch and +370.00/+5600.00 deactuation point pounds per square inch

**Contact Adjustment Type:**

External actuation point knob

**Contact Stimulus Rating:**

280.00 actuation point pounds per square inch and 5600.00 actuation point pounds per square inch and 370.00 deactuation point pounds per square inch and 5600.00 deactuation point pounds per square inch

**Contact Voltage Rating In Volts:**

460.0 ac at sea level first voltage

**Pressure Connector Type:**

Gasket seal, threaded internal single connection

**Media For Which Designed:**

Liquid

**Style Designator:**

Rectangular

**Thread Series Designator:**

Npt single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0