NSN 5930-01-198-1553



Pressure Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-01-198-1553 **Thread Class:** 2b all threaded hole **Inside Diameter:** 0.125 inches single connection **Overall Length:** 3.062 inches **Overall Diameter:** 3.125 inches **Distance Between Mounting Facility Centers:** 1.624 inches **Pressure Switch Type:** Differential **Operating Tempurature Rating:** Between -65.0 degrees fahrenheit and 165.0 degrees fahrenheit **Mounting Method:** Threaded hole **Contact Action Stimulus:** Decrease **Proof Pressure:** 15.00 inches of water

Thread Size:

0.190 inches all threaded hole

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

10.0 amperes resistive load third voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+0.15/+1.25 actuation point inches of water

Contact Voltage Rating In Volts:

480.0 ac at sea level first voltage

Pressure Connector Type:

Plain, threaded internal all connections

Frequency In Hertz:

60.0 third voltage

Media For Which Designed:

Gas

NSN 5930-01-198-1553

Pressure Switch - Page 2 of 2



Style	Designator:
,	

Cylindrical

Thread Series Designator:

Unf all threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0