

View Online at <https://aerobasegroup.com/nsn/5930-01-198-1553>

Thread Class:

2b all threaded hole

Inside Diameter:

0.125 inches single connection

Overall Length:

3.062 inches

Overall Diameter:

3.125 inches

Distance Between Mounting Facility Centers:

1.624 inches

Pressure Switch Type:

Differential

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 165.0 degrees fahrenheit

Mounting Method:

Threaded hole

Contact Action Stimulus:

Decrease

Proof Pressure:

15.00 inches of water

Thread Size:

0.190 inches all threaded hole

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

10.0 amperes resistive load third voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+0.15/+1.25 actuation point inches of water

Contact Voltage Rating In Volts:

480.0 ac at sea level first voltage

Pressure Connector Type:

Plain, threaded internal all connections

Frequency In Hertz:

60.0 third voltage

Media For Which Designed:

Gas

Style Designator:

Cylindrical

Thread Series Designator:

Unf all threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0