## NSN 5930-01-198-1816

Push Switch - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5930-01-196-1616
Body Style:
Bushing mounted
Hazardous Locations/environmental Protection:
Moisture resistant
Overall Height:
0.630 inches
Overall Width:
0.630 inches
Body Diameter:
0.630 inches
Bushing Length:
0.440 inches
Body Length:
1.280 inches
Case Material:
Metal
Actuator Diameter:
0.630 inches
Actuator Height:
0.800 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
White single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Features Provided:
Actuator seal
Thready Qty Per Inch (tpi):
32
Thread Size:
0.469 inches
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
2.000 amperes resistive dc and 1.500 amperes inductive dc and 1.000 amperes lamp dc and 2.000 amperes resistive ac and 1.500 amperes
inductive ac and 1.000 amperes lamp ac

**Precious Material And Location:** 

Contact and terminal surfaces gold

## **NSN 5930-01-198-1816**Push Switch - Page 2 of 2



inread Series Designator:
Uns
Terminal Type And Quantity:
8 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0