NSN 5930-01-198-1816

Push Switch - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5930-01-196-1616
Body Style:
Bushing mounted
Hazardous Locations/environmental Protection:
Moisture resistant
Overall Height:
0.630 inches
Overall Width:
0.630 inches
Body Diameter:
0.630 inches
Bushing Length:
0.440 inches
Body Length:
1.280 inches
Case Material:
Metal
Actuator Diameter:
0.630 inches
Actuator Height:
0.800 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
White single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Features Provided:
Actuator seal
Thready Qty Per Inch (tpi):
32
Thread Size:
0.469 inches
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
2.000 amperes resistive dc and 1.500 amperes inductive dc and 1.000 amperes lamp dc and 2.000 amperes resistive ac and 1.500 amperes
inductive ac and 1.000 amperes lamp ac

Precious Material And Location:

Contact and terminal surfaces gold

NSN 5930-01-198-1816Push Switch - Page 2 of 2



inread Series Designator:
Uns
Terminal Type And Quantity:
8 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0