

View Online at <https://aerobasegroup.com/nsn/5930-01-198-6138>

Thread Class:

3a single pressure connection

Hazardous Locations/environmental Protection:

Dustproof and fungus resistant and humidity resistant and salt spray resistant and vibration resistant

Overall Length:

2.290 inches

Outside Diameter:

0.438 inches single connection

Body Length:

1.200 inches

Overall Diameter:

1.000 inches

Pressure Switch Type:

Differential

Width Across Flats:

1.000 inches

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 275.0 degrees fahrenheit

Mounting Method:

Input port

Contact Action Stimulus:

Increase

Proof Pressure:

600.00 pounds per square inch gage

Thread Size:

0.438 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

1000.00 pounds per square inch gage

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

7.0 amperes resistive load single voltage and 4.0 amperes inductive load single voltage and 2.5 amperes lamp load single voltage

Contact Adjustability:

Actuation point not adjustable, manual reset

Contact Stimulus Rating:

10.00 actuation point pounds per square inch

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0