## NSN 5930-01-198-6140

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-198-6140

**Overall Length:** 3.440 inches **Outside Diameter:** 0.125 inches single connection **Overall Diameter:** 2.030 inches **End Application:** 6115-00-450-5881 generator set, diese **Pressure Switch Type:** Differential **Operating Tempurature Rating:** Between -25.0 degrees fahrenheit and 125.0 degrees fahrenheit **Mounting Method:** Inlet connection Thready Qty Per Inch (tpi): 27 single pressure connection **Contact Action Stimulus:** Decrease **Proof Pressure:** 500.00 pounds per square inch **Thread Size:** 0.125 inches single pressure connection **Nonpile-up Contact Arrangement:** 4 two circuit, both positions maintained **Terminal Type:** Connector, receptacle **Contact Load Current Rating:** 10.0 amperes resistive load single voltage **Contact Adjustability:** Actuation point not adjustable and deactuation point not adjustable **Contact Stimulus Rating:** 28.00 deactuation point pounds per square inch and 41.00 deactuation point pounds per square inch **Contact Voltage Rating In Volts:** 23.0 dc at sea level single voltage **Pressure Connector Type:** External seat-gasket seal, threaded external single connection Media For Which Designed: Gas or liquid

## Cylindrical

**Style Designator:** 

**Thread Series Designator:** 

Npt single pressure connection

## NSN 5930-01-198-6140

Pressure Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0