

View Online at <https://aerobasegroup.com/nsn/5930-01-199-2914>

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

Overall Length:

3.635 inches

Overall Height:

0.750 inches

Overall Width:

0.750 inches

Body Width:

0.679 inches

Body Height:

0.679 inches

Case Material:

Metal

Actuator Length:

0.530 inches

Actuator Style:

Rectangular

Actuator Height:

0.100 inches

Actuator Width:

0.530 inches

Actuator Color:

Black single actuator and black single actuator

Illuminated Actuator Color:

White single actuator and amber single actuator

Actuator Inscription:

Off single actuator

Actuator Color Sequence:

Left half of actuator black right half of actuator black

Illuminated Actuator Color Sequence:

Left half of actuator white right half of actuator amber

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

2.950 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Vertical split lens

Nonpile-up Contact Arrangement:

3 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac and 1.000 amperes lamp ac

Special Features:

Left half of screen contains a pair of 0.020 in. W white "visible" lines filled with 0.020 dia. Dots, right half of screen contains legend, screen split vertically

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0