

View Online at <https://aerobasegroup.com/nsn/5930-01-199-7178>

Overall Length:

8.200 inches

Overall Height:

3.280 inches

Overall Width:

5.500 inches

Unthreaded Mounting Hole Diameter:

0.312 inches

Pressure Switch Type:

Gage

Mounting Facility Circle Radius:

4.750 inches

Operating Temperature Rating:

Between -30.0 degrees fahrenheit and 160.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Thready Qty Per Inch (tpi):

18 first threaded hole

Contact Action Stimulus:

Increase

Proof Pressure:

15000.00 pounds per square inch gage

Thread Size:

0.750 inches second threaded hole

Mounting Facility Pattern:

Four position circular

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained

Terminal Type:

Screw

Contact Load Current Rating:

5.0 amperes resistive load fifth voltage and 40.0 milliamperes inductive load fifth voltage

Contact Adjustability:

Actuation point adjustable, preset and deactuation point adjustable, preset

Contact Adjustment Range:

+1000.00/+10000.00 actuation point pounds per square inch gage and +800.00/+9000.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

External actuation point hex nut with scale

Contact Stimulus Rating:

800.00 actuation point pounds per square inch gage and 900.00 actuation point pounds per square inch gage and 1000.00 deactuation point pounds per square inch gage

Contact Voltage Rating In Volts:

600.0 ac at sea level fourth voltage

Pressure Connector Type:

Plain, threaded internal single connection

Frequency In Hertz:

60.0 third voltage

Media For Which Designed:

Liquid

Style Designator:

Cylindrical w/mounting lugs

Thread Series Designator:

Npt second threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0